Custom Code Configuration Example (eSituation.13)

```
<!------------------------------------------------------------------>
```
`<!-- eCustomConfiguration section -->`
```
<!------------------------------------------------------------------>

        <eCustomConfiguration>
                <eCustomConfiguration.CustomGroup CustomElementID="itRecord.001">
                        <eCustomConfiguration.01>itRecord.001</eCustomConfiguration.01>
                        <eCustomConfiguration.02>Incident ID (Export Only)</eCustomConfiguration.02>
                        <eCustomConfiguration.03>9902005</eCustomConfiguration.03>
                        <eCustomConfiguration.04>9923001</eCustomConfiguration.04>
                        <eCustomConfiguration.05>9903007</eCustomConfiguration.05>
                </eCustomConfiguration.CustomGroup>
                <eCustomConfiguration.CustomGroup CustomElementID="eSituation.13">
                        <eCustomConfiguration.01
nemsisElement="eSituation.13">eSituation.13</eCustomConfiguration.01>
                        <eCustomConfiguration.02>The acuity of the patient's condition upon EMS arrival at
the scene.</eCustomConfiguration.02>
                        <eCustomConfiguration.03>9902009</eCustomConfiguration.03>
                        <eCustomConfiguration.04>9923001</eCustomConfiguration.04>
                        <eCustomConfiguration.05>9903003</eCustomConfiguration.05>
                        <eCustomConfiguration.06 nemsisCode="2813003" customValueDescription="Priority
2">it2813.101</eCustomConfiguration.06>
                </eCustomConfiguration.CustomGroup>
        </eCustomConfiguration>
<!------------------------------------------------------------------>
```
```
<!-- PatientCareReport section -->
<!-- NOTE: because eSituation.13 is a Nationally-required element
        in the XML you must provide a "real" value here.  Upon import,
        if a value is found in eCustomResults for this element, the
        value provided here will get "overwritten" -->
```
```
<!------------------------------------------------------------------>

        <eSituation.13>2813003</eSituation.13>

<!------------------------------------------------------------------>
```
`<!-- eCustomResults section -->`
```
<!------------------------------------------------------------------>

        <eCustomResults>
                <eCustomResults.ResultsGroup>
                        <eCustomResults.01>122416</eCustomResults.01>
                        <eCustomResults.02>itRecord.001</eCustomResults.02>
                </eCustomResults.ResultsGroup>
                <eCustomResults.ResultsGroup>
                        <eCustomResults.01>it2813.101</eCustomResults.01>
                        <eCustomResults.02>eSituation.13</eCustomResults.02>
                </eCustomResults.ResultsGroup>
        </eCustomResults>
```